

TAM QUICK ENGINE SPECIFICATION

specs_nis_tb42.xlsx

Nissan TB42				
4169 C.C.				
BORE	STROKE	FIRING	MAIN	ROD
3.78	3.78	1-5-3-6-2-4		
SPARK PLUG TYPE	SPARK PLUG GAP	DISTRIBUTOR GAP	IGN.TIMING IDLE SPEED	OIL CAPACITY WITH FILTER
LOCATION		TORQUE VALUES		LOCATION
	FT. LB.			FT. LB.
Main brg.caps			Oil pan drain plug	
Rod brg. caps			Oil pump bolt	
Cyl. head bolts			Rocker arm nut	
Cam sprocket bolt			Rckr. shaft brckt.bolt	
Crank pulley bolt			Side cover bolt	
Flywheel bolt			Spark plug	
Flywheel housing			Water outlet bolt	
Manifold bolt and nut			Water pump bolt	
Oil pan bolt			Wtr.pmp.pulley bolt	
		PISTON		
Diameter				
Pin diameter				
		RINGS		
Ring gap-Top				
Ring gap-2nd				
Ring gap-3rd				
		CRANKSHAFT		
Main journal dia.				
Main run clearance				
End play				
		CAMSHAFT		
Front journal dia.				
Center journal dia.				
Rear journal dia.				
		VALVES		
Intake length			Exhaust length	
Intake stem dia.			Exhaust stem dia.	
Intake head dia.			Exhaust head dia.	
Intake face angle			Exhaust face angle	
Intake clearance			Exhaust clearance	